

Product	Color	Thickness	Visible Light Transmission (VLT)	UV Rejection	Glare Reduction	Total Solar Energy Rejected	Infrared Rejection*
---------	-------	-----------	----------------------------------	--------------	-----------------	-----------------------------	---------------------

## Jet Black

Jet Black 5	Black	1.5 mils	5%	99%	95%	45%	12%
Jet Black 15	Black	1.5 mils	16%	99%	82%	41%	12%
Jet Black 20	Black	1.5 mils	22%	99%	78%	42%	12%
Jet Black 30	Black	1.5 mils	32%	99%	65%	36%	12%
Jet Black 35	Black	1.5 mils	34%	99%	62%	36%	12%
Jet Black 43	Black	1.5 mils	43%	99%	53%	33%	12%
Jet Black 50	Black	1.5 mils	51%	99%	45%	29%	12%
Jet Black 55	Black	1.5 mils	55%	99%	40%	29%	12%
Jet Black 70	Black	1.5 mils	70%	99%	23%	24%	12%
Jet Black 88	Black	1.5 mils	86%	99%	39%	27%	35%

## Hybrid Ore

Hybrid Ore 5	Black	1.5 mils	4%	99%	96%	59%	32%
Hybrid Ore 15	Black	1.5 mils	13%	99%	86%	53%	32%
Hybrid Ore 20	Black	1.5 mils	17%	99%	82%	53%	32%
Hybrid Ore 35	Black	1.5 mils	34%	99%	63%	49%	32%
Hybrid Ore 50	Black	1.5 mils	54%	99%	41%	36%	32%

## Ceramic

Ceramic 5	Black	1.5 mils	5%	99%	95%	66%	78%
Ceramic 15	Black	1.5 mils	15%	99%	83%	65%	78%
Ceramic 20	Black	1.5 mils	20%	99%	78%	64%	78%
Ceramic 30	Black	1.5 mils	30%	99%	67%	58%	78%
Ceramic 35	Black	1.5 mils	36%	99%	60%	59%	78%
Ceramic 45	Black	1.5 mils	46%	99%	50%	52%	78%
Ceramic 55	Black	1.5 mils	54%	99%	41%	50%	78%
Ceramic 70	Black	1.5 mils	68%	99%	27%	49%	85%

\*Infrared Rejection as measured at 1,025 nm.  
 All values are as applied to 1/8" (3mm) clear glass.